

## P2500S

Single-Feed Identification Printer  
at a Great Value

Rewrite and Full  
Color Printing

Single Feed for  
On-Demand Printing

Compact and Portable

Printer Driver  
Image Sharpening

3 Color LED Light  
Indicates Printer  
Status

Optional Magnetic  
Encoder



The *Polaroid* easy-to-use  
ID Card Printer

## Specifications

Print Mode	Color dye sublimation and monochrome thermal printing and rewritable technology	
Printing Speed	Approx: Color 35 seconds; mono 7 seconds	
Printing Side	Single-side	
Cards Supported	Card Size	ISO CR80 and CR79 .51mm to 1.02mm (20 mil to 40 mil)
	Card Material	PVC blank, magnetic stripe, self adhesive and SecureShield Patch cards
Card Storage Capacity (ISO CR80, ISO 7810)	N/A	
Interface	USB rev.1.1 (USB 2.0 compatible)	
Software Drivers	Compatible with Windows 7 <sup>®</sup> , Vista <sup>™</sup> , XP <sup>™</sup> , 2000 <sup>™</sup> and 2003 Server <sup>™</sup>	
Operating Environment	50°F to 85°F (10°C to 30°C)	
Power Supply	External power supply 100-240V 50-60Hz autoranging	
Weight	9.7 lbs. (4.4 kg)	
External Dimensions	10.6" x 8.4" x 9.1" (L x W x H); 270mm x 215mm x 233mm (L x W x H)	
Dye Film (options)	YMCKO	5 panel dye film, 300 images
	KO	Black and Overlay resin dye film, 600 images
	White resin (K)	White resin dye film, 1000 images
	Black resin (K)	Black resin dye film, 1000 images
	Blue resin (K)	Blue resin dye film, 1000 images
	Green resin (K)	Green resin dye film, 1000 images
	Gold resin (K)	Gold resin dye film, 1000 images
Card Security	The user has the option to print a SecureShield Overlay security watermark across the card surface. When used with the SecureShield Patch cards, one area of the SecureShield Overlay watermark is highlighted as a high visibility security seal. A choice of 5 fixed SecureShield Overlay patterns are selectable from the printer driver and the selected watermark is printed during the normal print cycle without adding cost.	
Rewritable Technology	Rewritable cards have one glossy side in PVC for color/monochrome dye sublimation printing and a matte finish rewritable side with a blue or black thermochromatic material that can be printed for up to 500 rewrite cycles.	
Warranty	Two year manufacturer's warranty including all parts and labor	

### Mag Option

Magnetic stripe encoder available.

### Hand-Feed Feature

Hand-feed card slot at the front provides users with one-off card printing.

### Compact Design

Small footprint for easy portability.

**Polaroid introduces its P2500S card printer—ID issuance has never been more economical for companies issuing ID cards in low volumes. The single-feed P2500S offers advanced features at a great value bundled in this easy-to-use card printer. The P2500S provides visual security for printed cards with its SecureShield Overlay anti-copying watermark. Unlike expensive holographic laminates, the Polaroid SecureShield Overlay does not add printing cost. Choose from (5) security designs to protect your cards or turn off the security feature if desired. Fine tune the printing controls such as image sharpening and coloring through the intuitive printer driver.**

## SecureShield Technology

SecureShield Overlay	Print anti-copying watermark across the entire card surface that becomes visible when the card is viewed at an angle. The P2500S SecureShield Overlay features 5 standard designs.
SecureShield Patch	Print the SecureShield Overlay on the SecureShield Patch card stock.

### Standard SecureShield Overlay Patterns



1-866-ID PHOTO  
www.polaroid-id.com

Polaroid and Polaroid & Pixel are trademarks of PLR IP Holdings, LLC, used under license. All other trademarks are the property of the respective owner, who has not sponsored, endorsed or approved this product. PLR IP Holdings, LLC does not manufacture this product or provide any Manufacturer's Warranty or support.